



CRT-T5 Towable Core Drilling Machine

CRT-T5

The CRT-T5 is a self contained hydraulically driven diamond drilling trailer for taking core samples in roads or airport runways with concrete or asphalt surfaces. Rugged, compact, maneuverable coring trailer which out performs all manually fed or direct engine driven machines.

Key Features

- Up to 10 Hours of normal working is possible with the 20 litre fuel tank and 410 litre water tank.
- Drill strokes options of 700 mm, 1000 mm and 1200 mm with extension bars for deeper drilling.
- Diesel or Petrol engine
- Proportional drill feed control
- 'Remote handset control' allows for fast & safe coring.
- 'Unique' Soft Start Drilling feature ideal for in-experienced operators.
- 'Hydraulically operated stabilisers' controlled from handset.
- Power take-off facility (optional) for driving a hydraulic road breaker or hydraulic tamper.
- Unladen weight 950 Kgs, laden weight 1350 Kgs.
- 103 dB Maximum noise level.

Accessories

Accessories are not included in the price of main device (unless stated otherwise) and may be purchased separately if required.

Optional Extras

- Operator safety guarding / Single or Two-speed hydraulic drill motors
- Low vibration hydraulic tamper
- Mast mounted warning beacon

Specifications

Technical specifications are subject to change without notice.

Engine	20 kW Kohler Diesel or 15 kW Honda Petrol engine
Fuel Tank	20 Litres
Water Pump	12v D.C. on board
Water Tank	410 Litres

Hydraulic Reservoir	30 litres capacity
Hydraulic PTO	20 Litres /min @ 130 bar
Suspension / Tyres	Torsion bar (EEC.Spec) / Tyres 175 R
Lenght-Width-Height mm	3300 x 1750 x 2930 for Standard Mast
Height in Transport	Standard Mast 2930 mm
Tow Hitch	50mm (75Kg Nose Weight - Fully Laden) 13pin / 7pin light connector
Weight (approx.) Kg	850 - Unladen / 1350 - Laden
Drill Capacity	Up to 800 mm Diameter

Datasheet Version: 19.11/02